

BfS AutoStreamer - Liquid Fertiliser Applicator

The BfS AutoStreamer is a' Perfect Partner' for a **flow based** rate controller. To ensure the accurate application of liquid fertiliser the operator has only to enter the litres per hectare required, factor in the specific gravity (SG) and begin to apply. Changing the application rate is equally simple and undertaken from within the cab. The BfS AutoStreamer is manufactured in chemical resistant, glass reinforced plastic and easily fitted to most boom sprayers.

How does it work?

Using a clever quad-valve system the BfS AutoStreamer allows the operator to achieve, a ten-fold increase in flow rates from only a three-fold increase in pressure. As the liquid fertiliser enters the BfS AutoStreamer the flow is channeled into four individual outlets.

BfS AutoStreamer Features:

- Accurate placement of liquid fertiliser
- Minimises overlaps
- Full rate applied right up to the crop edge
- Variable rate application "on-the-go"
- Reduced crop scorch
- Allows application under a wide range of weather conditions
- No contamination of ditches and watercourses
- Protects hedgerow plants
- Better Nitrogen Use Efficiency
- Simple to use

 Fitting
 Part No.

 TeeJet / EF3 / Euro
 NFB500001

 Agrifac
 NFB500010

 Stabiliser band
 NFB300004



BfS AutoStreamer Application Chart

Litres per Hectare	Speed range in Kph, between 0.75 bar to 2.6 bar pressure														
	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
60															
120															
180															
240															
300															
400															
500															
600															
700															
800															
900															
1000															
1100															